

North American Fire Codes  
requires operators to  
Drain Static Electricity!

Stewart R Browne Mfg. Co.

# STATIC SURE Portable Static Monitoring

COMPLIES WITH NFPA 77 AND API RP2003

## ARE YOU SURE THAT YOU ARE PROPERLY GROUNDED WHEN TRANSFERRING FLAMMABLES?

ANY transfer of flammable liquids or solids generates a STATIC CHARGE that has the potential to cause explosions. Every year hundreds of fires and explosions are caused by static discharge when transferring flammables. Be sure you are safe with the STATIC-SURE LE600 Portable Static Monitoring System.

- Automatic illumination of a RED LED when an improper ground is in place.
- Three year average battery life (under normal operating conditions).
- Configurable to fit a variety of applications and locations.
- Economically priced to get you compliant at a low cost.
- Quick-Connect cables for fast and sure connections.
- Dust and Low Pressure Water Spray Resistant.
- Intrinsically Safe housing.

The **STATIC-SURE LE600** system **alerts** the operator if an improper static bond or improper ground is in effect. Thus, warning you, BEFORE a problem can start!



**STATIC-SURE** is an intrinsically safe portable static monitoring device designed to help you comply with safety regulations and maintain a safe working environment. When used with proper bonding and grounding cable-clamp assemblies **STATIC-SURE** will assist operators in determining that a static bond, or ground, has been achieved prior to handling flammable materials.

### OPTIONS

2 Ft. Cable with Lugs
2 Ft. Cable with REB-IP Clamp
2 Ft. Cable with GAT-P-IP Clamp
20 Ft. Coiled Cable with REB-P Clamp
20 Ft. Coiled Cable with GAT-P-IP
Terminal Dust Cover Caps
Wall Mounting Brackets
Carry-All Canvas Bag

### APPLICATIONS

Fuel Transfer (Military, Bulk sites)
Rail Cars and Trains
Maritime (Ships, Barges)
Chemical Distribution/Manufacturing
Medical Manufacturing Facilities
Ink and Paint Shops/Manufacturers
Oil & Gas - Onshore and Off Shore
Vacuum Trucking Operations

### DATA

cULus Listed
Class I, Div 1. Groups A, B, C, D and Class II, Div. 1, Groups F, G.
Temperature Code: T4
Ambient Temperature: -40F to +122F
Resistance Limit: 10 Ohm
Battery Life Expectancy: 3 Years
Environmental Rating: IP65

## Stewart R. Browne Manufacturing Company, Inc.

**Mail:** P.O. Box 500008 Atlanta, GA 31150

**Ship:** 1165 Hightower Trail, Atlanta, GA 30350

**Web:** <http://www.srbrowne.com>

**Phone:** (770) 993-9600

**Fax:** (770) 594-7758

**e-Mail:** [info@srbrowne.com](mailto:info@srbrowne.com)



PORTABLE SAFETY LIGHTING  
STATIC GROUNDING SYSTEMS  
SINCE 1918

# STATIC SURE GROUNDING SYSTEM COMPONENT OPTIONS



LE600-2REB



LE600-20REB



LE600-2GAT



LE600-20GAT



LE600-Base



LE600-2LUGS



SBR50R-LE600i

To configure your STATIC SURE™ grounding system start with the LE600-Base unit and add a cable assembly for each port (the cables are interchangeable with either port). Our reel option, part number SBR50R-LE600i, is a kit and includes the LE600 Base unit. The yellow cable assemblies are for the Ohm-Check configuration and DO NOT provide monitoring.



LE600-2FT-LUGS-G1S



Application




LE600-20REB-OHM

LE600-2REB-OHM



ACCESSORIES



**Stewart R. Browne**  
Manufacturing Company, Inc.

**Mail:** P.O. Box 500008 Atlanta, GA 31150  
**Ship:** 1165 Hightower Trail, Atlanta, GA 30350  
**Web:** <http://www.srbrowne.com>

**Phone:** (770) 993-9600  
**Fax:** (770) 594-7758  
**e-Mail:** [info@srbrowne.com](mailto:info@srbrowne.com)

**STEWART R. BROWNE**  
MANUFACTURING COMPANY  
PORTABLE SAFETY LIGHTING  
STATIC GROUNDING SYSTEMS  
SINCE 1918